



www.consistent.in



IP SURVEILLANCE CAMERA

4MP IP DOME WARM CAMERA



CT-CM-IDW4MP

- 4MP Resolution, Full Color, Plastic Body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Smart 265, H.265, H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperature 0°C ~ 50°C
- Working humidity 0%~90%

4MP IP BULLET WARM CAMERA



CT-CM-IBW4MP

- 44 MP Resolution , Full Color , Plastic body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Smart H.265, H.265, H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- working temperature 0°C ~ 50°C
- Working Humidity 0%~90%

4MP IP EAGLE DOME CAMERA



CT-CM-IDW4MPE

- 4 MP Resolution Video Output, Metal Body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Smart H.265, H.265, H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperature 0°C ~ 50°C
- Working humidity 0%~90%

4MP IP EAGLE BULLET CAMERA



CT-CM-IBW4MPE

- 4 MP Resolution Video Output, Metal Body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Smart H.265, H.265, H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- working temperature 0°C ~ 50°C
- working humidity 0%~90%

4MP IP NIGHT HAWK DOME CAMERA



CT-CM-IDM4MP

- 4 MP Resolution Video Output, Metal Body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Support : humanoid /motion and vehicle detection
- Smart H.265, H.265, H.264
- Support 3D DNR , BLC and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- Working @ 0.01LUX
- POE In-built, Power 12V/1A

4MP IP NIGHT HAWK BULLET CAMERA



CT-CM-IBM4MP

- 4 MP Resolution Video Output, Metal Body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Support : humanoid /motion and vehicle detection
- Smart H.265, H.265, H.264
- Support 3D DNR , BLC and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- Working @ 0.01LUX
- POE In-built, Power 12V/1A

6MP IP DOME WARM CAMERA



CT-CM-IDW6MP

- 6 MP Resolution , Full Color , Full Metal body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Smart H.265, H.265, H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- working temperature 0°C ~ 50°C
- working humidity 0%~90%

6MP IP WARM BULLET CAMERA



CT-CM-IBW6MP

- 6 MP Resolution , Full Color , Full Metal body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Smart H.265, H.265, H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperature 0°C ~ 50°C
- Working humidity 0%~90%

8MP IP WARM Dome CAMERA



CT-CM-IDW8MP

- 8 MP Resolution , Full Color , Full Metal body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Smart H.265, H.265, H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperature 0°C ~ 50°C
- Working humidity 0%~90%

8MP IP WARM BULLET CAMERA



CT-CM-IBW8MP

- 8 MP Resolution , Full Color , Full Metal body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Smart H.265, H.265, H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperature 0°C ~ 50°C
- Working humidity 0%~90%

IP SURVEILLANCE CAMERA

TWO WAY BULLET/DOME CAMERA WARM 4 MP



CT-CM-IBW4MPTW/CT-CM-IDW4MPTW

- 4 MP Resolution Video Output, Metal Body
- High Quality, 4mm Fixed Lens
- Built-in Mic and Speaker (Two-way)
- Color Distance Upto 20 mtr
- Smart H.265, H.265,H.264
- Support 3D DNR , BLC and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperture 0°C ~ 50°C
- Working humidity 0%~90%

6 MM IP CAMERA WARM BULLET



CT-CM-IBW6MM

- 4 MP Resolution , Full Color , Plastic body
- High Quality, 6mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 30 mtr
- Smart H.265, H.265,H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperature 0°C ~ 50°C
- Working humidity 0%~90%

8 MM IP CAMERA WARM BULLET



CT-CM-IBW8MM

- 4 MP Resolution , Full Color , Plastic body
- High Quality, 8mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 40 mtr
- Smart H.265, H.265,H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperature 0°C ~ 50°C
- Working humidity 0%~90%

12 MM IP CAMERA WARM BULLET



CT-CM-IBW12MM

- 4 MP Resolution , Full Color , Plastic body
- High Quality, 12mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 60 mtr
- Smart H.265, H.265,H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperature 0°C ~ 50°C
- Working humidity 0%~90%

SMART CAMERA

2MP + 2MP 4G LINKAGE MINI



CT-CM-4MLPT

- Support 3D DNR and Digital WDR
- support ONVIF ,EMAIL,NTP service ,RTSP Protocol
- support 12v/POE option
- working temperature 0°C ~ 50°C
- working humidity 0%~90%
- Dual Intelligent Camera
- 2MP + 2MP resolution for clear & sharp visuals
- Upto 256GB SD Card Support

3MP + 3MP 4G SOLAR LINKAGE



CT-CM-6MLPT

- Two Way Audio Intercom
- Human detection and Human tracking with Push Notifications
- IP66 Rated Dust & Water Resistant
- Mobile App/PC Monitoring with Easy Cloud
- 10X Digital Zoom
- Dual Intelligent Camera
- 3MP+3MP 4GSolarLinkage PT Camera
- Upto 256GB SD Card Support

4G CCTV CAMERA DOME



CT-CM-IDD4G3M

- Two Way Audio Intercom
- Human detection and Human tracking with Push Notifications
- IP66 Rated Dust & Water Resistant
- Mobile App/PC Monitoring with Easy Cloud
- 10X Digital Zoom
- 3MP (2304 x 1296)Resolution, Dome Camera
- All Time Color Vision
- Full Duplex Audio Intercom(Built-in High Sensitivity Mic & Speaker)
- Area Motion Detection, Human Detection, Push Real time Notification on the Application
- Mobile Notification on Human & Motion Detection
- Customized Pre-recorded Voice Alarm

4G CCTV CAMERA BULLET



CT-CM-IBD4G3M

- Support Micro SD Card upto 256GB & Cloud Storage(Optional)
- Compression: H.264/H.265/H.265+
- 4G connection QR code for Easy to add camera in the app
- Monitoring: Mobile/PC Software(Esecloud)
- Alexa Support
- 3MP (2304 x 1296)Resolution, Bullet Camera
- All Time Color Vision
- Full Duplex Audio Intercom(Built-in High Sensitivity Mic & Speaker)
- Area Motion Detection, Human Detection, Push Real time Notification on the Application
- Mobile Notification on Human & Motion Detection
- Customized Pre-recorded Voice Alarm

3MP + 3MP 4G SOLAR LINKAGE(New)



CT-CM-6MLPTH

- 3MP + 3MP Dual Linkage Solar Camera
- H.265 Video Compression
- Dual-Light Night Vision
- Pan/Tilt Tracking~Auto human tracking
- Smart AI Human Detection
- Two-Way Audio - Full duplex with improved echo cancellation
- 4G Connectivity, LTE full-band support
- AOV (Always ON Video) 24 X 7 Recording
- 8Ww solar panel, ultra long standby time & long recording
- App : HiEasy

4G SOLAR PT WITH 4 LENS LINKAGE CAMERA



CT-CM-12MLPTH

- 3MP* 4 lens linkage solar camera
- Pan/ Tilt Tracking - Auto human tracking
- H.265 / H.265 Video Compression
- Dual light day & night full color vision
- Smart AI Human Detection
- Two-Way Audio - Full duplex with improved echo cancellation
- 4G Connectivity, LTE full-band support
- AOV (Always ON Video) 24 X 7 Recording
- App: HiEasy

SMART SURVEILLANCE CAMERA

4G SOLAR 3MP+3MP LINKAGE PTZ CAMERA



CT-CM-6MLPTHX

- 3MP+3MP, resolution with 16X optical zoom
- Pan/ Tilt Tracking - Auto human tracking
- H.265 / H.265 Video Compression
- Dual light day & night full color vision
- Smart AI Human Detection
- Two-Way Audio - Full duplex with improved echo cancellation
- 4G Connectivity, LTE full-band support
- AOV (Always ON Video) 24 X 7 Recording
- App: HiEasy

3MP+3MP 4G MINI PT CAMERA



CT-CM-6M4GPTH

- 3MP + 3MP Dual Linkage Camera
- H.265 Video Compression
- Dual-Light Night Vision
- Pan/Tilt Tracking-Auto human tracking
- Smart AI Human Detection
- Two-Way Audio - Full duplex with improved echo cancellation
- 4G Connectivity, LTE full-band support
- App : HiEasy

WIRELESS WIFI 3MP MINI CAMERA



CT-CM-W3MPHRP

- Support Micro SD Card upto 256GB & Cloud Storage(Optional)
- Compression: H.264/H.265/H.265+
- 4G connection QR code for Easy to add camera in the app
- Monitoring: Mobile/PC Software(Easy cloud)
- Alexa Support
- 3 MP HD wifi Camera
- AP Mode Available for local View

WIRELESS WIFI 2MP MINI CAMERA



CT-CM-W2MPATC

- Smart Mode Supportable
- Human detection and Human tracking with Push Notifications
- Support ONVIF, TF Card upto 256GB and Cloud Storage
- Two Way Communication
- view any time, anywhere via Easy Cloud Mobile App
- 2 MP HD wi-fi Camera
- AP Mode Available for local View

ANALOG CCTV CAMERA

CCTV HD CAMERA 2MP BULLET-W



CTCMHBW2MPA

- 1/3", 2.0MP, CMOS Sensor, Dome
- Lens 3.6mm Fixed Lens
- Color Night Vision upto 20 meters
- Warm Starlight Arrey
- 3D Noise Reduction, Multi Angle Adjustable
- Operating Temperature -100C - 500C
- 12V Weather resistance, Plastic Body

CCTV HD CAMERA 2MP DOME-W



CTCMHDW2MPA

- 1/3", 2.0MP, CMOS Sensor, Dome
- Lens 3.6mm Fixed Lens
- Color Night Vision upto 20 meters
- Warm Starlight Arrey
- 3D Noise Reduction, Multi Angle Adjustable
- Operating Temperature -10°C - 50°C
- 12V Weather resistance, Plastic Body

5MP CCTV AHD BULLET CAMERA



CTCMHBW5MPA

- 1/3", 5.0 MP@12.5 FPS Default , CMOS Sensor, Dome
- Lens 3.6 mm Fixed lens
- Color Night Vision Upto 20 meters
- Support: Audio (TVI , CVI)
- Warm Starlight Arrey
- 3D Noise Reduction , Multi Angle Adjustable
- Oprating Temperperature -10°C - 50°C
- 12V/1A weather rasistance , Plastic Body

5MP CCTV AHD DOME CAMERA



CTCMHDW5MPA

- 1/3", 5.0 MP@12.5 FPS Default , CMOS Sensor, Dome
- Lens 3.6 mm Fixed lens
- Color Night Vision Upto 20 meters
- Support: Audio (TVI , CVI)
- Warm Starlight Arrey
- 3D Noise Reduction , Multi Angle Adjustable
- Oprating Temperperature -10°C - 50°C
- 12V/1A weather rasistance , Plastic Body

PoE SWITCH-P2P & ROUTER

POE SWITCH 4/8CH GOLD



C-4P-2UE-G/C-8P-2UE-G

- 4*10/100 mbps PoE Port ; 2*10/100 mbps Uplink Port ;250mtr distance
- Support ; IEEE802.3AF/AT
- Whole Power ; 120W(52V 2.3A)
- All Port Supported by MDI /MDX Auto and self Negotiation
- Supply 4* 10/100 MBPS adaptive height speed forwarding data packet , non lose port
- Support IEEE802.3x flow control for full duplex and back pressure for half duplex mode
- Each port max.power supply reached 30 W

POE SWITCH 8CH



CG-8P-2UG-2S

- 8*1000Mbps PoE ports, 2*1000Mbps,Ethernet port, 2 SFP slot
- 1-8 Port: 250m Distance PoE Switch
- Support IEEE802.3af/at
- Support restrain network storm
- All port supported by MDI/MDIX auto flip & self-negotiation
- Built-in power supply
- Maximum power of single PoE port: 30 W
- Maximum PoE power: 150W
- Adopts store-and-forward architecture
- Support lightning protection 4KV

POE SWITCH 16CH



CT-16P-2UG-1S-D

- 4*10/100 mbps PoE Port ; 2*10/100 mbps Uplink Port ;250mtr distance
- Support ; IEEE802.3AF/AT
- Whole Power ; 120W(52V 2.3A)
- All Port Supported by MDI /MDX Auto and self Negotiation
- Supply 4* 10/100 MBPS adaptive height speed forwarding data packet , non lose port
- Support IEEE802.3x flow control for full duplex and back pressure for half duplex mode
- Each port max.power supply reached 30 W

CLOUD PoE



CT-8P-CE

- 8 × 10/100/1000 Mbps PoE Ports (IEEE802.3af/at)
- Total PoE Power: 120W (Max. 30W per port)
- 16 Gbps Switching Capacity
- 4M Large Cache for stable data transmission
- Supports VLAN, QoS, IGMP Snooping, PoE Management
- Lightning Protection 6KV
- Supports Web / Telnet / CLI / Cloud Management
- MAC Address Table: 8K
- Working Temperature: -10°C ~ 55°C
- Dimensions: 200 × 118 × 44 mm (bare metal)

4G ROUTER

WIFI 6 4G ROUTER VELOCITY



CT-4GR-TAW6

- Single LAN PORT + Wifi
- Range Upto 120 mtr
- External Tripple Antenna , High Speed Network Device
- 4G LTE Support (with fallback to 3G/2G)
- All GSM Network Support with lose Network
- Extra Features: SMS, USSD, Failover mode, DDNS, Port forwarding, Guest Wi-Fi
- 4G/5G SIM Supported
- Port, Auto Switching LAN /WAN
- Ethernet Ports : 1-4 LAN ports (10/100 Mbps or Gigabit), 1 WAN port (optional)

WI-FI 6 4G ROUTER



CT-4GR-TAW6

- 4G LTE + Wi-Fi 6 Support – Works with 802.11ax/b/g (2.4GHz)
- Fast Speeds – LTE up to 150Mbps (Download), 50Mbps (Upload)
- 4G LTE + Wi-Fi 6 Support – Works with 802.11ax/b/g (2.4GHz)
- SIM Flexibility – Supports SIM + e-SIM + e-SIM
- Smart Indicators–Signal, Wi-Fi, & LAN status lights
- Low Power Requirement – 5V / 1A input
- WiFi Coverage: Up to 50m indoors / 100m outdoors (depends on environment)
- Stable Coverage–External Antennas (4G ×1, Wi-Fi ×1)

WIRELESS BRIDGE (P2P)

1KM WIRELESS BRIDGE



CT-WP2PDT01

- Frequency Band 2.4 GHz
- Transmission SpeedUp to 300 Mbps
- RangeUp to 1 km (LOS)
- Encryption WPA2
- Power Supply 24V Passive PoE
- Operating Temperature-30°C to +60°C
- Enclosure Rating IP65
- Mounting Options Pole and wall mount

5 KM WIRELESS BRIDGE



CT-WP2PDT05

- Frequency Band 2.4 GHz/5 GHz
- Transmission SpeedUp to 900 Mbps
- RangeUp to 5 km (LOS)
- Encryption WPA2
- Power Supply 24V Passive PoE
- Operating Temperature-30°C to +60°C
- Enclosure Rating IP65
- Mounting Options Pole and wall mount

DIGITAL VIDEO RECORDER

4 CHANNEL DIGITAL VIDEO RECORDER



CT-DVR-CH004

- 4 CH TVI /AHD/CVI 1080P/ 1080P Lite/ 720P/ 720P Lite/WD1 video input
- 4 CH DVR supports 2 CH IP video input by default
- Playback : 4 CH simultaneously playback
- Search: time slice, time, event, tag search
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote
- Support 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS

8 CHANNEL DIGITAL VIDEO RECORDER



CT-DVR-CH008

- 8 CH TVI /AHD/CVI 1080P/ 1080P Lite/ 720P/ 720P Lite/WD1 video input
- 8 CH DVR supports 2 CH IP video input by default
- 8 CH DVR: 8CH analog video input can be switched to 8CH IP video input
- Playback : 8CH simultaneously playback
- Search: time slice, time, event, tag search
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Support 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QR Code scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Android OS
- Dual stream technology for local storage with high definition, remote
- Remote control via Web or CMS : preview, playback, backup, PTZ and configuration

16 CHANNEL DIGITAL VIDEO RECORDER



CT-DVR-CH016

- 16 CH TVI / AHD/CVI 1080P/1080PLite/720P/720P Lite/WD1 video input
- Supports 2CH 5MP/4MP/3MP/1080P/960P/720PIP video input by default
- H.265/H.264 coding
- Multi-mode recording: manual / timed / motion / AI recording
- Playback : 16 CH simultaneously playback
- Search: time slice, time, event, tag search
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web or CMS : preview, playback, backup, PTZ and configuration
- Support remote network transmission and remote surveillance with mobile device
- Support 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Powerful mobile surveillance by smart phones with iOS andAndriod OS
- Support NAT function and QRCode scanning by mobile phones Powerful mobile

HYBRID VIDEO RECORDER

4 CHANNEL HYBRID VIDEO RECORDER



CT-HVR-CH04

- 4 Channel HVR – Supports AHD/TVI/CVI/CVBS/IP self-recognition
- Hybrid Input – HD Analog + HD Network + All IP mode support
- Dual Display Output – HDMI & VGA up to 1080P resolution
- Smart Video Compression – H.264/H.265 Encoding – High compression, saves storage space
- Remote Monitoring – P2P, QR code scan, iOS & Android App support
- ONVIF 2.4 Support – Compatible with third-party IP cameras
- Audio Functions – Supports coaxial audio input & extended intercom
- Smart Recording & Playback – Time/event retrieval, motion detection playback
- Storage & Backup – Supports 1 × SATA HDD (up to 8TB), USB & network backup
- Network Ready – RJ45 Ethernet interface for remote access
- Power Efficient – 12V/2A, <15W (exclusive of HDD)

8 CHANNEL HYBRID VIDEO RECORDER



CT-HVR-CH08

- 8 Channel Hybrid Video Recorder – Supports AHD/TVI/CVI/CVBS/IP cameras
- Hybrid Input Modes – Analog + IP or pure IP (up to 16×5MP)
- Dual Display Output – HDMI & VGA outputs up to 1080P resolution
- Smart Video Compression – H.264/H.265 for efficient storage
- Remote Monitoring – P2P, QR code scan, iOS & Android App supported
- ONVIF 2.4 Support – Compatible with third-party IP cameras
- Audio Support – 8ch coaxial audio input, intercom, extended RCA output
- Smart Recording & Playback – Motion detection playback, event & timeline search
- Storage & Backup – 1 × SATA HDD up to 8TB + USB/Network backup
- Network Ready – RJ45 (10/100M) Ethernet interface
- Power Efficient – 12V/2A adapter, <15W consumption (without HDD)
- Reliable Operation – Works in -5°C to +55°C, 10–90% humidity

16 CHANNEL HYBRID VIDEO RECORDER



CT-HVR-CH16

- 16 Channel DVR – Supports AHD/TVI/CVI/CVBS/IP video input
- Full HD Display – HDMI & VGA outputs up to 1080P resolution
- H.264/H.265 Video Compression – Saves bandwidth & storage space
- Remote Monitoring – P2P, QR code scan, iOS & Android App support
- ONVIF Support – Works with compatible third-party IP cameras
- Audio Functions – Multiple channel input, intercom & output support
- Smart Recording & Playback – Motion detection, event search, timeline playback
- Supports SATA HDD (up to 8TB) + USB/Network backup
- Network Ready – RJ45 Ethernet port for cloud & remote access
- Power Supply: 12V DC, low consumption design
- Durable Performance – Reliable in -5°C to +55°C operating range

NETWORK VIDEO RECORDER

4 CHANNEL NETWORK VIDEO RECORDER



CT-NVR-CH004

- Support 4 CH 8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/DI/CIF IP
- video input H.265S/H.265+/H.265/H.264 coding
- Multi-type recording: manual / timed / motion / sensor / POS / AI recording
- Search : time slice, time, event, tag, smart search
- Playback : 4 CH simultaneous playback
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web Client or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- HD output, true high resolution display
- Support NAT function and QR Code scanning by mobile phones

8 CHANNEL NETWORK VIDEO RECORDER



CT-NVR-CH008

- Support 8 CH 8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/DI/CIF IP
- video input H.265S/H.265+/H.265/H.264 coding
- Multi-type recording: manual / timed / motion / sensor / POS / AI recording
- Search : time slice, time, event, tag, smart search
- Playback : 8CH simultaneous playback
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web Client or CMS : playback, backup, PTZ & configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- HD output, true high resolution display
- Support NAT function and QR Code scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Android OS

16 CHANNEL NETWORK VIDEO RECORDER



CT-NVR-CH0016

- Supports 16/ CH 12MP / 9MP / 8MP / 6MP / 5MP / 4MP / 3MP / 1080P
- video input H.265S/H.265+/H.265/H.264 coding
- Multi-type recording: manual / timed / motion / sensor / POS / AI recording
- Search : time slice, time, event, tag, smart search
- Playback : 16CH simultaneous playback
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web Client or CMS : playback, backup, PTZ & configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- 4K HD output, true high resolution display
- Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Android OS

NETWORK VIDEO RECORDER

10 CHANNEL NETWORK VIDEO RECORDER



CT-NVR-CH310

- Support 10ch 4K access
- Support ONVIF protocol
- Video output VGA*1, HDMI*1
- Image decoding H.264/H.265
- Image display 1/4/6/9/10 screen
- Voice format G.711U, G.711A, G.726
- Supports 1 HDD, with a maximum capacity of 8TB
- Support remote monitor and playback via Easy VMS
- Power DC12V 5A
- APP Hi-Easy can be used for remote monitoring and playback of video

16 CHANNEL NETWORK VIDEO RECORDER



CT-NVR-CH416

- Support 16ch 4K access
- Support ONVIF protocol
- Video output VGA*1, HDMI*1
- Image decoding H.264/H.265
- Image display 1/4/6/9/10 screen
- Voice format G.711U, G.711A, G.726
- Supports 1 HDD, with a maximum capacity of 8TB
- Support remote monitor and playback via Easy VMS
- Power DC12V 5A
- APP Hi-Easy can be used for remote monitoring and playback of video

36 CHANNEL NETWORK VIDEO RECORDER



CT-NVR-CH536

- Support 36ch 4k output
- Support ONVIF protocol
- Video output VGA*1, HDMI*1
- Image decoding H.264/H.265
- Image display 1/4/6/9/10/16 screen
- Voice format G.711U, G.711A, G.726
- Support AI functions such as human figure detection, face capture, and face comparison
- Support 2 hard disk access, each support maximum 8TB HDD
- Support remote monitor and playback via Easy VMS
- Support 3.5mm audio interface, expandable input and output
- Power DC12V 5A
- APP HiEasy can be used for remote monitoring and play back of video



4 Channel



4k HDMI video
Output



Intelligent
Analytics

ETHERNET & DESKTOP SWITCH

CONSISTENT DESKTOP SWITCH



CT-DS-05PN

- 5x10/100-TX ports
- Comply with IEEE802.3, IEEE802.3u standards
- 5V1A power supply
- Support desktop and wall mount install on
- Plug and play, no need to configure
- Maximum transmission distance can up to 100m
- Support 2KV surge protec on, 4KV ESD protect on

CONSISTENT DESKTOP SWITCH



CT-DS-05PG

- 5x10/100/1000-TX ports
- Comply with IEEE802.3, IEEE802.3u standards
- 5V1A power supply
- Support desktop and wall mount installa on
- Plug and play, no need to configure
- Maximum transmission distance can up to 100m
- Support 2KV surge protec on, 4KV ESD protec on

CONSISTENT DESKTOP SWITCH



CT-DS-08PG

- 8x10/100/1000-TX port
- Comply with IEEE802.3, IEEE802.3u standard
- 5V1A power supply
- Support desktop and wall mount install on
- Plug and play, no need to configure
- Maximum transmission distance can up to 100m
- Support 2KV surge protec on, 4KV ESD protec on

CONSISTENT DESKTOP SWITCH



CT-DS-08PN

- 8x10/100-TX ports
- Comply with IEEE802.3, IEEE802.3u standards
- 5V1A power supply
- Support desktop and wall mount install on
- Plug and play, no need to configure
- Maximum transmission distance can up to 100m
- Support 2KV surge protec on, 4KV ESD protec on

CONSISTENT DESKTOP SWITCH



CT-DS-16PG

- 16x10/100/1000Base-TX switch
- Comply with IEEE802.3, IEEE802.3u standards
- Support IEEE802.3X full-duplex flow control; support Auto MDI/MDIX
- External 12VDC/1A power adapter
- Support desktop and wall mount installation
- Plug and play, with 2KV Surge & 4KV ESD Protection
- Maximum transmission distance can up to 100m

CCA AND CAT6 CABLE


3+1 CCTV Cable



xxxxxxx

- 70 Meters / 90 Meters
- 90 Meter Gold Series
- 90 Meter (Outdoor)
- 90 Yards
- Length Bundle
- All Weather PVC
- Cable With
- Extra Density Shield
- Long Term Durability

CAT6 305M CCA CABLE



CT-CC-100M/CT-CC-100M-OD

- CCA Conductor (Copper Clad Aluminium)
- Supports 10/100/1000 Mbps
- Bandwidth up to 250 Mhz
- Twisted Pair – Low Interference
- Durable Outer Jacket
- Ideal for CCTV & Networking Use

CAT6 100M COPPER CABLE



CT-CC-100MC

- CAT-6 UTP Cable
- 100 Meters Length
- 100% Copper Conductor (CU)
- Supports Up to 1 Gbps
- Bandwidth Up to 250 Mhz
- Suitable for Gigabit Networks

CAT6 305M CCA CABLE



CT-CC-305M

- CAT-6 UTP Cable
- Length: 305 Meters
- Conductor: CCA (Copper-Clad Aluminum)
- Bandwidth: Up to 250 MHz
- Supports Gigabit Ethernet (1 Gbps)
- Suitable for LAN, CCTV, and Networking

CAT6 305M COPPER CABLE



CT-CC-305MC/CT-CC-305MC-OD

- High-quality CAT6 Copper Cable
- 305 meters length
- Supports up to 250 MHz bandwidth
- Suitable for 10/100/1000 Mbps Ethernet networks
- Pure copper conductors for optimal performance

CAT6 CCA 305M OD CABLE



CT-CC-305M-OD

- CAT6 CCA (Copper-Clad Aluminum) Cable
- 305 meters length
- Supports up to 250 MHz bandwidth
- Suitable for 10/100/1000 Mbps Ethernet networks
- Durable outer jacket (OD) for protection and longevity

CAT6 COPPER 100M OD CABLE



CTCC-100MC-OD

- High-quality CAT6 Copper Cable
- 100 meters length
- Supports up to 250 MHz bandwidth
- Suitable for 10/100/1000 Mbps Ethernet networks
- Durable outer jacket (OD) for protection and longevity

CAT6 CCA 305M OD CABLE



CT-CC-305M-OD

- High-quality 3+1 core design for stable signal transmission
- Length: 70 meters per roll
- Durable insulation for long-lasting performance
- Flexible and easy to install
- Suitable for CCTV and networking applications
- Corrosion-resistant copper conductors for reliable connectivity

3+1 90M CABLE GOLD



CT-CC-90MG

- Premium 3+1 core design for reliable signal transmission
- Gold-coated conductors for enhanced conductivity and corrosion resistance
- Length: 90 meters per roll
- Flexible and easy to install for CCTV and networking use
- Durable insulation ensures long-lasting performance

3+1 90M OUTDOOR CABLE



CT-CC-90M-OD

- 3+1 core design for stable signal transmission
- Outdoor-grade cable with UV-resistant and weatherproof jacket
- Length: 90 meters per roll
- Flexible and easy to install for CCTV and networking applications
- Corrosion-resistant copper conductors for reliable performance

CCA - CAT6 CABLE AND RACK

3+1 CCTV Cable



CT-CC-90Y

- 3+1 core design for reliable signal transmission
- High-quality copper conductors for stable connectivity
- Length: 90 meters per roll
- Durable insulation for long-lasting performance
- Flexible and easy to install for CCTV and networking applications

CCA CABLE


CAT6 305M CCA CABLE



CT-CC-305-E

- CAT-6 UTP Cable – 305 Meters
- Conductor: CCA (Copper-Clad Aluminum)
- Imported Quality – Reliable Performance
- Bandwidth: Up to 250 Mhz
- Supports Gigabit Ethernet (1 Gbps)
- Ideal for LAN, CCTV & Networking Installations

CAT6 100M CCA CABLE



CT-CC-100-E

- CAT-6 UTP Cable – 100 Meters
- Conductor: CCA (Copper-Clad Aluminum)
- Imported Quality – Durable & Reliable
- Bandwidth: Up to 250 Mhz
- Supports Gigabit Ethernet (1 Gbps)
- Ideal for LAN, CCTV & Networking

RACK

DVR/NVR RACKS 2U & 4U FIXED RACKS



CT-NRM-2U/CT-NRM-4U

- Color : Grey
- Material : Metal
- Compatible Device: DVR/NVR
- Item Weight :2900grams (2U Rack)
- Mounting Type : Wall Mount
- Made With GI Metal and with 7-wauu processing power coating
- It come with security locks and fitting accessories.
- Cable Managers are provided for better cable management

DVR/NVR 6U RACKS



CT-NRM-6U

- Heavy-duty metal body for strong support
- Compact 6U size – ideal for professional installations
- Easy wall or cabinet mounting
- Durable powder-coated finish for long life
- Suitable for DVR, NVR, PoE switches & networking devices
- Dimensions: 356MM(W) × 550MM(D) × 305MM(H) (approx.)

DVR/NVR 4U RACKS



CT-NRM-4U

- Heavy-duty metal body for strong support
- Compact 4U size – ideal for larger setups
- Easy wall or cabinet mounting
- Durable powder-coated finish for long life
- Suitable for DVR, NVR, PoE switches & networking devices
- Dimensions: 450MM(W) × 350MM(D) × 240MM(H) (approx.)

DVR/NVR 2U RACK



CT-NRM-2U

- Heavy-duty metal body for strong support
- Compact 2U size – space-saving design
- Easy wall or cabinet mounting
- Durable powder-coated finish for long life
- Ideal for DVR, NVR, PoE switch & networking devices
- Dimensions: 300MM(W) × 500MM(D) × 150MM(H) (approx.)

BNC-DC CABLE AND SMPS

BNC/DC CABLE

BNC CABLE



CT-BPG15

- High-quality coaxial cable with BNC connectors for reliable video transmission
- Superior shielding to minimize signal interference and noise
- Flexible and durable for easy installation
- Compatible with all standard CCTV cameras and DVRs
- Long-lasting performance with corrosion-resistant conductors

DC CABLE



CT-DPC05

- High-quality copper conductors for stable power transmission
- Flexible insulation for easy installation in tight spaces
- Corrosion-resistant & durable for long-lasting use
- Compatible with all CCTV cameras and power adapters
- Ensures reliable power supply for uninterrupted surveillance

BNC BRACE



CT-BPBW25

- High-quality coaxial cable with BNC connectors for stable video transmission
- Integrated brace design for added strength and durability
- Superior shielding to reduce interference and signal loss
- Flexible and easy to install for CCTV systems
- Long-lasting performance with corrosion-resistant conductors

CCTV SMPS

4/8 CH CCTV POWER SUPPLY MULTI



CT-CPS-04PG/CT-CPS-08PG

- 4/8-channel output for multiple CCTV cameras
- Stable and reliable power supply for uninterrupted surveillance
- Built-in short-circuit, overload, and surge protection
- Compact, durable, and easy-to-install design
- High-efficiency performance to save energy and ensure long life

CCTV POWER SUPPLY MULTI



CT-CPS-016PG

- 16-channel output for multiple CCTV cameras
- Stable and reliable power supply for uninterrupted surveillance
- Built-in short-circuit, overload, and surge protection
- Compact, durable, and easy-to-install design
- High-efficiency performance to save energy & ensure long life

4/8 CHANNEL MULTI SMPS



CT-CPS-4PG/CT-CPS-8PG

- 4/8 Channel Multi Output – Ideal for multiple CCTV cameras
- Stable power supply for uninterrupted performance
- In-built short circuit, overload & surge protection
- High efficiency for long life and low power loss
- Compact and durable metal body for better safety

16 CHANNEL SINGLE OUTPUT



CT-CPS-16PG

- 16 Channel Single Output – Ideal for large CCTV setups
- Stable and reliable power supply for smooth operation
- In-built short circuit, overload & surge protection
- High efficiency for long life and low power consumption
- Strong and durable metal body for maximum safety



Scan to View
Our Catalogue



Scan to Visit
Our Website



e-Store

Consistent Infosystems Private Limited

Corporate Office:

307, Shakuntala Building, 59, Nehru Place,
New Delhi 110 019. India.

Toll Free: 1800 103 4593

(9:00am to 6:00pm. Monday - Saturday.)

Email: info@consistent.in | Web: www.consistent.in



consistentinfosystems



consistent-india



consistentindia



consistentinfo1



Consistent Infosystems Pvt. Ltd.



+91 8929766306