





www.consistent.in



IP SURVEILLANCE CAMERA

4MP IP DOME WARM CAMERA



CT-CM-IDW4MP

- 4MP Resolution, Full Color, Plastic Body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Smart 265, H265, H264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperature 0°C ~ 50°C
- Working humidity 0%~90%

4MP IP BULLET WARM CAMERA



CT-CM-IBW4MP

- 44 MP Resolution , Full Color , Plastic body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Smart H.265, H.265, H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- working temperature 0°C ~ 50°C
- Working Humidity 0%~90%

4MP IP EAGLE DOME CAMERA



CT-CM-IDW4MPE

- 4 MP Resolution Video Output, Metal Body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Smart H.265, H.265, H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperature 0°C ~ 50°C
- Working humidity 0%~90%

4MP IP EAGLE BULLET CAMERA



CT-CM-IBW4MPE

- 4 MP Resolution Video Output, Metal Body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Smart H.265, H.265, H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- working temperature 0°C ~ 50°C
- working humidity 0%~90%

4MP IP NIGHT HAWK DOME CAMERA



CT-CM-IDM4MP

- 4 MP Resolution Video Output, Metal Body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Support : humanoid /motion and vehicle detection
- Smart H.265, H.265, H.264
- Support 3D DNR , BLC and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- Working @ 0.01LUX
- POE In-built, Power 12V/1A

4MP IP NIGHT HAWK BULLET CAMERA



CT-CM-IBM4MP

- 4 MP Resolution Video Output, Metal Body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Support : humanoid /motion and vehicle detection
- Smart H.265, H.265, H.264
- Support 3D DNR , BLC and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- Working @ 0.01LUX
- POE In-built, Power 12V/1A

6MP IP DOME WARM CAMERA



CT-CM-IDW6MP

- 6 MP Resolution , Full Color , Full Metal body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Smart H.265, H.265, H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- working temperature 0°C ~ 50°C
- working humidity 0%~90%

6MP IP WARM BULLET CAMERA



CT-CM-IBW6MP

- 6 MP Resolution , Full Color , Full Metal body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Smart H.265, H.265, H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperature 0°C ~ 50°C
- Working humidity 0%~90%

8MP IP WARM Dome CAMERA



CT-CM-IDW8MP

- 8 MP Resolution , Full Color , Full Metal body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Smart H.265, H.265, H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperature 0°C ~ 50°C
- Working humidity 0%~90%

8MP IP WARM BULLET CAMERA



CT-CM-IBW8MP

- 8 MP Resolution , Full Color , Full Metal body
- High Quality, 4mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 20 mtr
- Smart H.265, H.265, H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperature 0°C ~ 50°C
- Working humidity 0%~90%

IP SURVEILLANCE CAMERA

TWO WAY BULLET/DOME CAMERA WARM 4 MP



CT-CM-IBW4MPTW/CT-CM-IDW4MPTW

- 4 MP Resolution Video Output, Metal Body
- High Quality, 4mm Fixed Lens
- Built-in Mic and Speaker (Two-way)
- Color Distance Upto 20 mtr
- Smart H.265, H.265,H.264
- Support 3D DNR , BLC and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperture 0°C ~ 50°C
- Working humidity 0%~90%

6 MM IP CAMERA WARM BULLET



CT-CM-IBW6MM

- 4 MP Resolution , Full Color , Plastic body
- High Quality, 6mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 30 mtr
- Smart H.265, H.265,H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperature 0°C ~ 50°C
- Working humidity 0%~90%

8 MM IP CAMERA WARM BULLET



CT-CM-IBW8MM

- 4 MP Resolution , Full Color , Plastic body
- High Quality, 8mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 40 mtr
- Smart H.265, H.265,H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperature 0°C ~ 50°C
- Working humidity 0%~90%

12 MM IP CAMERA WARM BULLET



CT-CM-IBW12MM

- 4 MP Resolution , Full Color , Plastic body
- High Quality, 12mm Fixed Lens
- Built-in-Microphone
- Color Distance Upto 60 mtr
- Smart H.265, H.265,H.264
- Support 3D DNR and Digital WDR
- Support ONVIF , Access Third Party RTSP Protocol
- POE In-built, Power 12V/1A
- Working temperature 0°C ~ 50°C
- Working humidity 0%~90%

SMART CAMERA

2MP + 2MP 4G LINKAGE MINI



CT-CM-4MLPT

- Support 3D DNR and Digital WDR
- support ONVIF ,EMAIL,NTP service ,RTSP Protocol
- support 12v/POE option
- working temperature 0°C ~ 50°C
- working humidity 0%~90%
- Dual Intelligent Camera
- 2MP + 2MP resolution for clear & sharp visuals
- Upto 256GB SD Card Support
- Mobile Application: EseeCloud

3MP + 3MP 4G SOLAR LINKAGE



CT-CM-6MLPT

- Two Way Audio Intercom
- Human detection and Human tracking with Push Notifications
- IP66 Rated Dust & Water Resistant
- Mobile App/PC Monitoring with Easy Cloud 10X Digital Zoom
- Dual Intelligent Camera
- 3MP+3MP 4GSolarLinkage PT Camera
- Upto 256GB SD Card Support
- Mobile Application: EseeCloud

4G CCTV CAMERA DOME



CT-CM-IDD4G3M

- Two Way Audio Intercom
- Human detection and Human tracking with Push Notifications
- IP66 Rated Dust & Water Resistant
- Mobile App/PC Monitoring with Easy Cloud
- 10X Digital Zoom
- 3MP (2304 x 1296)Resolution, Dome Camera
- All Time Color Vision
- Full Duplex Audio Intercom(Built-in High Sensitivity Mic & Speaker)
- Area Motion Detection, Human Detection, Push Real time Notification on the Application
- Mobile Notification on Human & Motion Detection
- Customized Pre-recorded Voice Alarm

4G CCTV CAMERA BULLET



CT-CM-IBD4G3M

- Support Micro SD Card upto 256GB & Cloud Storage(Optional)
- Compression: H.264/H.265/H.265+
- 4G connection QR code for Easy to add camera in the app
- Monitoring: Mobile/PC Software(Eseecloud)
- Alexa Support
- 3MP (2304 x 1296)Resolution, Bullet Camera
- All Time Color Vision
- Full Duplex Audio Intercom(Built-in High Sensitivity Mic & Speaker)
- Area Motion Detection, Human Detection, Push Real time Notification on the Application
- Mobile Notification on Human & Motion Detection
- Customized Pre-recorded Voice Alarm

3MP + 3MP 4G SOLAR LINKAGE(New)



CT-CM-6MLPTH

- 3MP + 3MP Dual Linkage Solar Camera
- H.265 Video Compression
- Dual-Light Night Vision
- Pan/Tilt Tracking~Auto human tracking
- Smart AI Human Detection
- Two-Way Audio - Full duplex with improved echo cancellation
- 4G Connectivity, LTE full-band support
- AOV (Always ON Video) 24 X 7 Recording
- 8Ww solar panel, ultra long standby time & long recording
- App : HiEasy

4G SOLAR PT WITH 4 LENS LINKAGE CAMERA



CT-CM-12MLPTH

- 3MP* 4 lens linkage solar camera
- Pan/ Tilt Tracking - Auto human tracking
- H.265 / H.265 Video Compression
- Dual light day & night full color vision
- Smart AI Human Detection
- Two-Way Audio - Full duplex with improved echo cancellation
- 4G Connectivity, LTE full-band support
- AOV (Always ON Video) 24 X 7 Recording
- App: HiEasy

SMART SURVEILLANCE CAMERA

4G SOLAR 3MP+3MP LINKAGE PTZ CAMERA



CT-CM-6MLPTHX

- 3MP+3MP, resolution with 16X optical zoom
- Pan/ Tilt Tracking - Auto human tracking
- H.265 / H.265 Video Compression
- Dual light day & night full color vision
- Smart AI Human Detection
- Two-Way Audio - Full duplex with improved echo cancellation
- 4G Connectivity, LTE full-band support
- AOV (Always ON Video) 24 X 7 Recording
- App: HiEasy

3MP+3MP 4G MINI PT CAMERA



CT-CM-6M4GPTH

- 3MP + 3MP Dual Linkage Camera
- H.265 Video Compression
- Dual-Light Night Vision
- Pan/Tilt Tracking-Auto human tracking
- Smart AI Human Detection
- Two-Way Audio - Full duplex with improved echo cancellation
- 4G Connectivity, LTE full-band support
- App : HiEasy

WIRELESS WIFI 3MP MINI CAMERA



CT-CM-W3MPHRP

- Support Micro SD Card upto 256GB & Cloud Storage(Optional)
- Compression: H.264/H.265/H.265+
- 4G connection QR code for Easy to add camera in the app
- Monitoring: Mobile/PC Software(Easy cloud)
- Alexa Support
- 3 MP HD wifi Camera
- AP Mode Available for local View

WIRELESS WIFI 2MP MINI CAMERA



CT-CM-W2MPATC

- Smart Mode Supportable
- Human detection and Human tracking with Push Notifications
- Support ONVIF, TF Card upto 256GB and Cloud Storage
- Two Way Communication
- view any time, anywhere via Easy Cloud Mobile App
- 2 MP HD wi-fi Camera
- AP Mode Available for local View

ANALOG CCTV CAMERA

CCTV HD CAMERA 2MP BULLET-W



CTCMHBW2MPA

- 1/3", 2.0MP, CMOS Sensor, Dome
- Lens 3.6mm Fixed Lens
- Color Night Vision upto 20 meters
- Warm Starlight Arrey
- 3D Noise Reduction, Multi Angle Adjustable
- Operating Temperature -100C - 500C
- 12V Weather resistance, Plastic Body

CCTV HD CAMERA 2MP DOME-W



CTCMHDW2MPA

- 1/3", 2.0MP, CMOS Sensor, Dome
- Lens 3.6mm Fixed Lens
- Color Night Vision upto 20 meters
- Warm Starlight Arrey
- 3D Noise Reduction, Multi Angle Adjustable
- Operating Temperature -10°C - 50°C
- 12V Weather resistance, Plastic Body

5MP CCTV AHD BULLET CAMERA



CTCMHBW5MPA

- 1/3", 5.0 MP@12.5 FPS Default , CMOS Sensor, Dome
- Lens 3.6 mm Fixed lens
- Color Night Vision Upto 20 meters
- Support: Audio (TVI , CVI)
- Warm Starlight Arrey
- 3D Noise Reduction , Multi Angle Adjustable
- Oprating Temprerature -10°C - 50°C
- 12V/1A weather rasistance , Plastic Body

5MP CCTV AHD DOME CAMERA



CTCMHDW5MPA

- 1/3", 5.0 MP@12.5 FPS Default , CMOS Sensor, Dome
- Lens 3.6 mm Fixed lens
- Color Night Vision Upto 20 meters
- Support: Audio (TVI , CVI)
- Warm Starlight Arrey
- 3D Noise Reduction , Multi Angle Adjustable
- Oprating Temprerature -10°C - 50°C
- 12V/1A weather rasistance , Plastic Body

PoE SWITCH-P2P & ROUTER

POE SWITCH 4/8CH GOLD



C-4P-2UE-G/C-8P-2UE-G

- 4*10/100 mbps PoE Port ; 2*10/100 mbps Uplink Port ;250mtr distance
- Support ; IEEE802.3AF/AT
- Whole Power ; 120W(52V 2.3A)
- All Port Supported by MDI /MDX Auto and self Negotiation
- Supply 4* 10/100 MBPS adaptive height speed forwarding data packet , non lose port
- Support IEEE802.3x flow control for full duplex and back pressure for half duplex mode
- Each port max.power supply reached 30 W

POE SWITCH 8CH



CG-8P-2UG-2S

- 8*1000Mbps PoE ports, 2*1000Mbps,Ethernet port, 2 SFP slot
- 1-8 Port: 250m Distance PoE Switch
- Support IEEE802.3af/at
- Support restrain network storm
- All port supported by MDI/MDIX auto flip & self-negoaon
- Built-in power supply
- Maximum power of single PoE port: 30 W
- Maximum PoE power: 150W
- Adopts store-and-forward architecture
- Support lightning protection 4KV

POE SWITCH 16CH



CT-16P-2UG-1S-D

- 4*10/100 mbps PoE Port ; 2*10/100 mbps Uplink Port ;250mtr distance
- Support ; IEEE802.3AF/AT
- Whole Power ; 120W(52V 2.3A)
- All Port Supported by MDI /MDX Auto and self Negotiation
- Supply 4* 10/100 MBPS adaptive height speed forwarding data packet , non lose port
- Support IEEE802.3x flow control for full duplex and back pressure for half duplex mode
- Each port max.power supply reached 30 W

CLOUD PoE



CT-8P-CE

- 8 × 10/100/1000 Mbps PoE Ports (IEEE802.3af/at)
- Total PoE Power: 120W (Max. 30W per port)
- 16 Gbps Switching Capacity
- 4M Large Cache for stable data transmission
- Supports VLAN, QoS, IGMP Snooping, PoE Management
- Lightning Protection 6KV
- Supports Web / Telnet / CLI / Cloud Management
- MAC Address Table: 8K
- Working Temperature: -10°C ~ 55°C
- Dimensions: 200 × 118 × 44 mm (bare metal)

POE Switch



CG-4P-2UG-1S

- 4 × 10/100/1000 Mbps PoE Ports
- 2 × Gigabit Uplink Ports + 1 × SFP Port
- 100W Total PoE Power Budget
- Up to 30W PoE Output per Port
- Long-Range PoE up to 250m
- AI Watchdog Function
- Plug & Play

POE SWITCH



CG-8P-2UG-1S)

- 8 × 10/100/1000 Mbps PoE Ports
- 2 × Gigabit Uplink Ports + 1 × SFP Port
- 100W Total PoE Power Budget
- Up to 30W PoE Output per Port
- Long-Range PoE up to 250m
- AI Watchdog Function
- Plug & Play

POE SWITCH



C-8P-2UE-V

- 8 × 10/100 Mbps PoE Ports
- 2 × 10/100 Mbps Uplink Ports
- 100W Total PoE Power Budget
- Up to 30W PoE Output per Port
- Long-Range PoE up to 250m
- AI Watchdog
- Plug & Play

PoE Switch



C-8P-2UG

- 8 × 10/100 Mbps PoE Ports
- 2 × 100/1000 Mbps Uplink Ports
- 100W Total PoE Power Budget
- Up to 30W PoE Output per Port
- Long-Range PoE up to 250m
- AI Watchdog
- Plug & Play

PoE Switch



C-8P-2UG-1S

- 8 × 10/100 Mbps PoE Ports
- 2 × Gigabit Uplink Ports + 1 × SFP Port
- 100W Total PoE Power Budget
- Up to 30W PoE Output per Port
- Long-Range PoE up to 250m
- AI Watchdog
- Plug & Play

Consistent POE Extender



CT-PEX-103

- 4-Port PoE Extender (1 PoE IN + 3 PoE OUT)
- Expand One PoE Port into Three
- Power & Data Over a Single Ethernet Cable
- Plug-and-Play Installation
- No External Power Supply Required
- Ideal for IP Cameras & Access Points

4G ROUTER

WIFI 6 4G ROUTER VELOCITY



CT-4GR-TAW6

- Single LAN PORT + Wifi
- Range Upto 120 mtr
- External Tripple Antenna , High Speed Network Device
- 4G LTE Support (with fallback to 3G/2G)
- All GSM Network Support with lose Network
- Extra Features: SMS, USSD, Failover mode, DDNS, Port forwarding, Guest Wi-Fi
- 4G/5G SIM Supported
- Port, Auto Switching LAN /WAN
- Ethernet Ports : 1-4 LAN ports (10/100 Mbps or Gigabit), 1 WAN port (optional)

4G ROUTER



CT-4GR-DAWI

- 4G LTE + Wi-Fi 6 Support – Works with 802.11ax/b/g (2.4GHz)
- Fast Speeds – LTE up to 150Mbps (Download), 50Mbps (Upload)
- 4G LTE + Wi-Fi 6 Support – Works with 802.11ax/b/g (2.4GHz)
- SIM Flexibility – Supports SIM + e-SIM + e-SIM
- Smart Indicators–Signal, Wi-Fi, & LAN status lights
- Low Power Requirement – 5V / 1A input
- WiFi Coverage: Up to 50m indoors / 100m outdoors (depends on environment)
- Stable Coverage–External Antennas (4G ×1, Wi-Fi ×1)

WIFI 4G ROUTER VELOX



CT-V4GR-TAW6

- Wi-Fi 6 Technology
- 4G/5G SIM Plug & Play
- Supports All GSM SIM Cards
- Up to 300 Mbps High-Speed Internet
- Supports Up to 32 Users
- Triple External High-Gain Antennas
- Ideal for CCTV, Home & Office
- RJ45 LAN Port
- Compact & Easy to Install

WIFI 6 4G WIFI ROUTER VELORA



CT-4GR-FAW6

- 4 Antina 5 DBI
- 5G Sim Supported
- Router , With
- 1 LAN Port ,
- 25 User Supported

WIRELESS BRIDGE (P2P)

1KM WIRELESS BRIDGE



CT-WP2PDT01

- Frequency Band 2.4 GHz
- Transmission SpeedUp to 300 Mbps
- RangeUp to 1 km (LOS)
- Encryption WPA2
- Power Supply 24V Passive PoE
- Operating Temperature-30°C to +60°C
- Enclosure Rating IP65
- Mounting Options Pole and wall mount

5 KM WIRELESS BRIDGE



CT-WP2PDT05

- Frequency Band 2.4 GHz/5 Ghz
- Transmission SpeedUp to 900 Mbps
- RangeUp to 5 km (LOS)
- Encryption WPA2
- Power Supply 24V Passive PoE
- Operating Temperature-30°C to +60°C
- Enclosure Rating IP65
- Mounting Options Pole and wall mount

5KM WIRELESS BRIDGE



CT-WP2PDTG5

- Frequency: 5 Ghz
- Maximum Range: Up to 5 KM
- Wireless Speed: Up to 900 Mbps
- Application: CCTV, Internet Sharing, Office-to-Office, Campus Networking
- Installation: Fast, cable-free deployment
- Benefit: Reliable, high-speed, long-distance wireless connectivity
- Remote App : HiCloudIoT

DIGITAL VIDEO RECORDER

4 CHANNEL DIGITAL VIDEO RECORDER



CT-DVR-CH004

- 4 CH TVI /AHD/CVI 1080P/ 1080P Lite/ 720P/ 720P Lite/WD1 video input
- 4 CH DVR supports 2 CH IP video input by default
- Playback : 4 CH simultaneously playback
- Search: time slice, time, event, tag search
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote
- Support 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS

8 CHANNEL DIGITAL VIDEO RECORDER



CT-DVR-CH008

- 8 CH TVI /AHD/CVI 1080P/ 1080P Lite/ 720P/ 720P Lite/WD1 video input
- 8 CH DVR supports 2 CH IP video input by default
- 8 CH DVR: 8CH analog video input can be switched to 8CH IP video input
- Playback : 8CH simultaneously playback
- Search: time slice, time, event, tag search
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Support 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QR Code scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Android OS
- Dual stream technology for local storage with high definition, remote
- Remote control via Web or CMS : preview, playback, backup, PTZ and configuration

16 CHANNEL DIGITAL VIDEO RECORDER



CT-DVR-CH016

- 16 CH TVI / AHD/CVI 1080P/1080PLite/720P/720P Lite/WD1 video input
- Supports 2CH 5MP/4MP/3MP/1080P/960P/720PIP video input by default
- H.265/H.264 coding
- Multi-mode recording: manual / timed / motion / AI recording
- Playback : 16 CH simultaneously playback
- Search: time slice, time, event, tag search
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web or CMS : preview, playback, backup, PTZ and configuration
- Support remote network transmission and remote surveillance with mobile device
- Support 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Powerful mobile surveillance by smart phones with iOS andAndriod OS
- Support NAT function and QRCode scanning by mobile phones Powerful mobile

HYBRID VIDEO RECORDER

4 CHANNEL HYBRID VIDEO RECORDER



CT-HVR-CH004

- 4 Channel HVR – Supports AHD/TVI/CVI/CVBS/IP self-recognition
- Hybrid Input – HD Analog + HD Network + All IP mode support
- Dual Display Output – HDMI & VGA up to 1080P resolution
- Smart Video Compression – H.264/H.265 Encoding – High compression, saves storage space
- Remote Monitoring – P2P, QR code scan, iOS & Android App support
- ONVIF 2.4 Support – Compatible with third-party IP cameras
- Audio Functions – Supports coaxial audio input & extended intercom
- Smart Recording & Playback – Time/event retrieval, motion detection playback
- Storage & Backup – Supports 1 × SATA HDD (up to 8TB), USB & network backup
- Network Ready – RJ45 Ethernet interface for remote access
- Power Efficient – 12V/2A, <15W (exclusive of HDD)

8 CHANNEL HYBRID VIDEO RECORDER



CT-HVR-CH008

- 8 Channel Hybrid Video Recorder – Supports AHD/TVI/CVI/CVBS/IP cameras
- Hybrid Input Modes – Analog + IP or pure IP (up to 16×5MP)
- Dual Display Output – HDMI & VGA outputs up to 1080P resolution
- Smart Video Compression – H.264/H.265 for efficient storage
- Remote Monitoring – P2P, QR code scan, iOS & Android App supported
- ONVIF 2.4 Support – Compatible with third-party IP cameras
- Audio Support – 8ch coaxial audio input, intercom, extended RCA output
- Smart Recording & Playback – Motion detection playback, event & timeline search
- Storage & Backup – 1 × SATA HDD up to 8TB + USB/Network backup
- Network Ready – RJ45 (10/100M) Ethernet interface
- Power Efficient – 12V/2A adapter, <15W consumption (without HDD)
- Reliable Operation – Works in -5°C to +55°C, 10–90% humidity

16 CHANNEL HYBRID VIDEO RECORDER



CT-HVR-CH016

- 16 Channel DVR – Supports AHD/TVI/CVI/CVBS/IP video input
- Full HD Display – HDMI & VGA outputs up to 1080P resolution
- H.264/H.265 Video Compression – Saves bandwidth & storage space
- Remote Monitoring – P2P, QR code scan, iOS & Android App support
- ONVIF Support – Works with compatible third-party IP cameras
- Audio Functions – Multiple channel input, intercom & output support
- Smart Recording & Playback – Motion detection, event search, timeline playback
- Supports SATA HDD (up to 8TB) + USB/Network backup
- Network Ready – RJ45 Ethernet port for cloud & remote access
- Power Supply: 12V DC, low consumption design
- Durable Performance – Reliable in -5°C to +55°C operating range

4 CHANNEL NETWORK VIDEO RECORDER



CT-NVR-CH004

- Support 4 CH 8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/DI/CIF IP
- video input H.265S/H.265+/H.265/H.264 coding
- Multi-type recording: manual / timed / motion / sensor / POS / AI recording
- Search : time slice, time, event, tag, smart search
- Playback : 4 CH simultaneous playback
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web Client or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- HD output, true high resolution display
- Support NAT function and QR Code scanning by mobile phones

8 CHANNEL NETWORK VIDEO RECORDER



CT-NVR-CH008

- Support 8 CH 8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/DI/CIF IP
- video input H.265S/H.265+/H.265/H.264 coding
- Multi-type recording: manual / timed / motion / sensor / POS / AI recording
- Search : time slice, time, event, tag, smart search
- Playback : 8CH simultaneous playback
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web Client or CMS : playback, backup, PTZ & configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- HD output, true high resolution display
- Support NAT function and QR Code scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Android OS

10 CHANNEL NETWORK VIDEO RECORDER



CT-NVR-CH310

- Support 10ch 4K access
- Support ONVIF protocol
- Video output VGA*1, HDMI*1
- Image decoding H.264/H.265
- Image display 1/4/6/9/10 screen
- Voice format G.711U, G.711A, G.726
- Supports 1 HDD, with a maximum capacity of 8TB
- Support remote monitor and playback via Easy VMS
- Power DC12V 5A
- APP Hi-Easy can be used for remote monitoring and playback of video



NETWORK VIDEO RECORDER

16 CHANNEL NETWORK VIDEO RECORDER



CT-NVR-CH416

- Support 16ch 4K access
- Support ONVIF protocol
- Video output VGA*1, HDMI*1
- Image decoding H.264/H.265
- Image display 1/4/6/9/10 screen
- Voice format G.711U,G.711A,G.726
- Supports 1 HDD, with a maximum capacity of 8TB
- Support remote monitor and playback via Easy VMS
- Power DC12V 5A
- APP Hi-Easy can be used for remote monitoring and playback of video

36 CHANNEL NETWORK VIDEO RECORDER



CT-NVR-CH536

- Support 36ch 4k output
- Support ONVIF protocol
- Video output VGA*1, HDMI*1
- Image decoding H.264/H.265
- Image display 1/4/6/9/10/16 screen
- Voice format G.711U,G.711A,G.726
- Support AI functions such as human figure detection, face capture, and face comparison
- Support 2 hard disk access, each support maximum 14TB HDD
- Support remote monitor and playback via Easy VMS
- Support 3.5mm audio interface, expandable input and output
- Power DC12V 5A
- APP HiEasy can be used for remote monitoring and play back of video



4 Channel



4k HDMI video
Output



Intelligent
Analytics

ETHERNET & DESKTOP SWITCH

CONSISTENT DESKTOP SWITCH



CT-DS-05PN

- 5x10/100-TX ports
- Comply with IEEE802.3, IEEE802.3u standards
- 5V1A power supply
- Support desktop and wall mount install on
- Plug and play, no need to configure
- Maximum transmission distance can up to 100m
- Support 2KV surge protec on, 4KV ESD protect on

CONSISTENT DESKTOP SWITCH



CT-DS-05PG

- 5x10/100/1000-TX ports
- Comply with IEEE802.3, IEEE802.3u standards
- 5V1A power supply
- Support desktop and wall mount installa on
- Plug and play, no need to configure
- Maximum transmission distance can up to 100m
- Support 2KV surge protec on, 4KV ESD protec on

CONSISTENT DESKTOP SWITCH



CT-DS-08PG

- 8x10/100/1000-TX port
- Comply with IEEE802.3, IEEE802.3u standard
- 5V1A power supply
- Support desktop and wall mount install on
- Plug and play, no need to configure
- Maximum transmission distance can up to 100m
- Support 2KV surge protec on, 4KV ESD protec on

CONSISTENT DESKTOP SWITCH



CT-DS-08PN

- 8x10/100-TX ports
- Comply with IEEE802.3, IEEE802.3u standards
- 5V1A power supply
- Support desktop and wall mount install on
- Plug and play, no need to configure
- Maximum transmission distance can up to 100m
- Support 2KV surge protec on, 4KV ESD protec on

CONSISTENT DESKTOP SWITCH



CT-DS-16PG

- 16x10/100/1000Base-TX switch
- Comply with IEEE802.3, IEEE802.3u standards
- Support IEEE802.3X full-duplex flow control; support Auto MDI/MDIX
- External 12VDC/1A power adapter
- Support desktop and wall mount installation
- Plug and play, with 2KV Surge & 4KV ESD Protection
- Maximum transmission distance can up to 100m

CCA AND CAT6 CABLE

3+1 CCTV Cable



CT-CC-70M/90M

- 70 Meters / 90 Meters
- 90 Meter Gold Series
- 90 Meter (Outdoor)
- 90 Yards
- Length Bundle
- All Weather PVC
- Cable With
- Extra Density Shield
- Long Term Durability

CAT6 100M CCA CABLE



CT-CC-100M/CT-CC-100M-OD

- CCA Conductor (Copper Clad Aluminium)
- Supports 10/100/1000 Mbps
- Bandwidth up to 250 Mhz
- Twisted Pair – Low Interference
- Durable Outer Jacket
- Ideal for CCTV & Networking Use

CAT6 100M COPPER CABLE



CT-CC-100MC

- CAT-6 UTP Cable
- 100 Meters Length
- 100% Copper Conductor (CU)
- Supports Up to 1 Gbps
- Bandwidth Up to 250 Mhz
- Suitable for Gigabit Networks

CAT6 305M CCA CABLE



CT-CC-305M

- CAT-6 UTP Cable
- Length: 305 Meters
- Conductor: CCA (Copper-Clad Aluminum)
- Bandwidth: Up to 250 MHz
- Supports Gigabit Ethernet (1 Gbps)
- Suitable for LAN, CCTV, and Networking

CAT6 305M COPPER CABLE



CT-CC-305MC/CT-CC-305MC-OD

- High-quality CAT6 Copper Cable
- 305 meters length
- Supports up to 250 MHz bandwidth
- Suitable for 10/100/1000 Mbps Ethernet networks
- Pure copper conductors for optimal performance

CAT6 CCA 305M OD CABLE



CT-CC-305M-OD

- CAT6 CCA (Copper-Clad Aluminum) Cable
- 305 meters length
- Supports up to 250 MHz bandwidth
- Suitable for 10/100/1000 Mbps Ethernet networks
- Durable outer jacket (OD) for protection and longevity

CAT6 COPPER 100M OD CABLE



CTCC-100MC-OD

- High-quality CAT6 Copper Cable
- 100 meters length
- Supports up to 250 MHz bandwidth
- Suitable for 10/100/1000 Mbps Ethernet networks
- Durable outer jacket (OD) for protection and longevity

CAT6 CCA 305M OD CABLE



CT-CC-305M-OD

- High-quality 3+1 core design for stable signal transmission
- Length: 70 meters per roll
- Durable insulation for long-lasting performance
- Flexible and easy to install
- Suitable for CCTV and networking applications
- Corrosion-resistant copper conductors for reliable connectivity

3+1 90M CABLE GOLD



CT-CC-90MG

- Premium 3+1 core design for reliable signal transmission
- Gold-coated conductors for enhanced conductivity and corrosion resistance
- Length: 90 meters per roll
- Flexible and easy to install for CCTV and networking use
- Durable insulation ensures long-lasting performance

3+1 90M OUTDOOR CABLE



CT-CC-90M-OD

- 3+1 core design for stable signal transmission
- Outdoor-grade cable with UV-resistant and weatherproof jacket
- Length: 90 meters per roll
- Flexible and easy to install for CCTV and networking applications
- Corrosion-resistant copper conductors for reliable performance

CCA - CAT6 CABLE AND RACK

3+1 CCTV Cable



CT-CC-90Y

- 3+1 core design for reliable signal transmission
- High-quality copper conductors for stable connectivity
- Length: 90 meters per roll
- Durable insulation for long-lasting performance
- Flexible and easy to install for CCTV and networking applications

CCTV CABLE

3+1 70M CABLE



CT-CC-70M

3+1 Copper wire
(20,14/43)
36 Alloy Braiding

3+1 70M CABLE



CT-CC-70MG

3+1 CCA wire Video
copper (20,14/43)
36 Alloy Braiding

CCA CABLE


CAT6 305M CCA CABLE



CT-CC-305M-E

- CAT-6 UTP Cable – 305 Meters
- Conductor: CCA (Copper-Clad Aluminum)
- Imported Quality – Reliable Performance
- Bandwidth: Up to 250 Mhz
- Supports Gigabit Ethernet (1 Gbps)
- Ideal for LAN, CCTV & Networking Installations

CAT6 100M CCA CABLE



CT-CC-100M-E

- CAT-6 UTP Cable – 100 Meters
- Conductor: CCA (Copper-Clad Aluminum)
- Imported Quality – Durable & Reliable
- Bandwidth: Up to 250 Mhz
- Supports Gigabit Ethernet (1 Gbps)
- Ideal for LAN, CCTV & Networking

CAT6 305M CCA CABLE



CT-CC-305M-E (GREY)

- CAT-6 UTP Cable – 305 Meters
- Conductor: CCA (Copper-Clad Aluminum)
- Imported Quality – Reliable Performance
- Bandwidth: Up to 250 Mhz
- Supports Gigabit Ethernet (1 Gbps)
- Ideal for LAN, CCTV & Networking Installations

NETWORK RACK

Consistent Network Rack



CT-NRM-2U

- 2u Rack
- 350*500*150mm
- 5 Thickness
- Foldable Rack

Consistent Network Rack



CT-NRM-4U

- 4u Rack
- 550*350*255mm
- 5 Thickness
- Foldable Rack

Consistent Network Rack



CT-NRM-6U

- 6u Rack
- 550*355*305mm
- 5 Thickness
- Foldable Rack

Consistent Network Rack



CT-NRM-9U

- 9u Rack
- 550*400*460mm
- 5 Thickness
- Foldable Rack

Consistent Network Rack



CT-NRM-NF-2U

- 2u Rack
- 350*500*150mm
- 5 Thickness
- Foldable Rack

Consistent Network Rack



CT-NRM-NF-4U

- 4u Rack
- 550*355*305mm
- 5 Thickness
- Foldable Rack

Consistent Network Rack(Gold)



CT-NRM-2UG

- 2u Rack
- 350*500*150mm
- 40 Thickness
- Foldable Rack

Consistent Network Rack(Gold)



CT-NRM-4UG

- 4u Rack
- 550*355*305mm
- 40 Thickness
- Foldable Rack

CAT6 PATCH CORD & POWER ADAPTER

PATCH CORD

CON CAT6 PATCH CORD 10M



CT-PC100

- CCA Cable
- 10m Length

CON CAT6 PATCH CORD 5M



CT-PC050

- CCA Cable
- 5m Length

CON CAT6 PATCH CORD 3M



CT-PC030

- CCA Cable
- 3m Length

CON CAT6 PATCH CORD 1.5M



CT-PC015

- CCA Cable
- 1.5m Length

POWER ADAPTER

CON POWER ADAPTER



CT-PA-1202

- Input Voltage: 110–290V AC
- Output: 12V DC, 2A
- Wide Input Voltage Range
- Stable & Reliable Power Output
- Compact & Durable Design
- Suitable for CCTV Cameras, Routers, LED Strips & Other 12V Devices


CON POWER ADAPTER



CT-PA-1203

- Input Voltage: 110–290V AC
- Output: 12V DC, 3A
- Wide Input Voltage Range
- Stable & Reliable Power Output
- Compact & Durable Design
- Suitable for CCTV Cameras, Routers, LED Strips & Other 12V Devices

CON POWER ADAPTER



CT-PA-1205

- Input Voltage: 110–290V AC
- Output: 12V DC, 5A
- Wide Input Voltage Range
- Stable & Reliable Power Output
- Compact & Durable Design
- Suitable for CCTV Cameras, Routers, LED Strips & Other 12V Devices

BNC-DC CABLE AND SMPS

BNC/DC CABLE


BNC PIGTAIL SEMI GOLD CONN.



CT-BPG15

- 20/40*2
- 7" Cord Length

DC PIGTAIL CONN.



CT-DPC05

- 20/38*2
- 7" Cord Length

BNC PIGTAIL PURE BRASS CONN.



CT-BPB20

- 20/38*2
- 7" Cord Length

BNC PURE BRASS CONN.



CT-BPBW25

- Connector BNC without wire

CCTV SMPS

4/8 CH CCTV POWER SUPPLY MULTI



CT-CPS-04PG/CT-CPS-08PG

- 4/8-channel **multi output** for multiple CCTV cameras
- Stable and reliable power supply for uninterrupted surveillance
- Built-in short-circuit, overload, and surge protection
- Compact, durable, and easy-to-install design
- High-efficiency performance to save energy and ensure long life

CCTV POWER SUPPLY MULTI



CT-CPS-16PG

- 16-channel **multi output** for multiple CCTV cameras
- Stable and reliable power supply for uninterrupted surveillance
- Built-in short-circuit, overload, and surge protection
- Compact, durable, and easy-to-install design
- High-efficiency performance to save energy & ensure long life

4/8 CHANNEL MULTI SMPS



CT-CPS-S4PG/CT-CPS-S8PG

- 4/8 Channel **single output** – Ideal for multiple CCTV cameras
- Stable power supply for uninterrupted performance
- In-built short circuit, overload & surge protection
- High efficiency for long life and low power loss
- Compact and durable metal body for better safety

16 CHANNEL SINGLE OUTPUT



CT-CPS-S16PG

- 16 Channel **single output** – Ideal for large CCTV setups
- Stable and reliable power supply for smooth operation
- In-built short circuit, overload & surge protection
- High efficiency for long life and low power consumption
- Strong and durable metal body for maximum safety

HDMI EXTENDER & MEDIA CONVERTER

HDMI EXTENDER

CON HDMI EXTENDER 60M



CT-HEX60M

- Extends HDMI Signal Up to 60 Meters
- Supports Full HD 1080p Resolution
- Uses Single CAT5e/CAT6 Ethernet Cable
- Plug-and-Play Installation
- Stable & Lossless Audio/Video Transmission
- Compact & Durable Design

CON HDMI EXTENDER 60M KVM



CT-HEX60MK

- 20/38*2
- 7" Cord Length

CON HDMI EXTENDER 150M KVM



CT-HEX150MK

- 20/40*2
- 7" Cord Length

MEDIA CONVERTER

CON MEDIA CONVERTER



CT-MC100N

- 10/100Mbps Fast Ethernet Media Converter
- Converts RJ45 to Fiber Optic Network
- Auto-Negotiation 10/100Mbps Ethernet Port
- Supports Single-Mode / Multi-Mode Fiber (as per model variant)
- Plug-and-Play Installation
- Stable & Reliable Data Transmission
- LED Status Indicators for Easy Monitoring

CON MEDIA CONVERTER



CT-MC100G

- 100/1000Mbps Fast Ethernet Media Converter
- Converts RJ45 to Fiber Optic Network
- Auto-Negotiation 10/100Mbps Ethernet Port
- Supports Single-Mode / Multi-Mode Fiber (as per model variant)
- Plug-and-Play Installation
- Stable & Reliable Data Transmission
- LED Status Indicators for Easy Monitoring

JUNCTION BOX, CCTV UPS & DOORBELL

JUNCTION BOX


CON JUNCTION BOX 4x4



CT-JB4401

- 4*4 Junction Box with Heavy quality fiber
- HD Camera

CON JUNCTION BOX 5x5



CT-JB5501

- 5*5 Junction Box with Heavy quality fiber
- HD Camera

CCTV UPS

CON CCTV UPS



CT-UPS-CH08

- Supports 8 CCTV Cameras + 8-Channel DVR + 4G Router
- Up to 2 Hours Power Backup
- Instant Power Switching (<1ms)
- Built-in Lithium-Ion Battery
- 8A High Output Capacity
- Short Circuit & Overload Protection
- Reverse Polarity & Low Battery Protection
- LED Status Indicators
- Specially Designed for CCTV Systems

CON MINI UPS



CT-UPS-M01

- 12V 2.5A Mini DC UPS
- Microcontroller-Based Design
- Instant Power Switching (<1ms)
- Zero Lag Backup
- Overload & Short Circuit Protection
- Deep Discharge Protection
- Overcharging Protection
- Low Battery Protection
- Ideal for CCTV Cameras, Routers & Networking Devices

DOORBELL

CON 3MP WIFI VIDEO DOOR BELL



CT-DB3MPW

- 3MP HD
- Instant Video Call
- Two-Way Talk
- Human Detection
- 256GB Storage
- Wi-Fi Enabled
- Voice Alarm
- Full-Duplex Audio
- 3D DNR
- IP65 Rated
- Remote Monitoring
- Mobile & PC Access

CABLE TESTER, MICRO SD SURVEILLANCE & CAMERA SPEAKER

SURVEILLANCE MICRO SD

Con 32GB Micro SD Surveillance



CTMS2032

- Up to 5,000 Hours Recording
- Perfect for 24x7 Surveillance
- Class 10 U3
- 100MB/s Speed
- 5-Year Warranty

Con 64GB Micro SD Surveillance



CTMS2064

- Up to 10,000 Hours Recording
- Perfect for 24x7 Surveillance
- Class 10 U3
- 100MB/s Speed
- 5-Year Warranty

Con 128GB Micro SD Surveillance



CTMS2128

- Up to 20,000 Hours Recording
- Perfect for 24x7 Surveillance
- Class 10 U3
- 100MB/s Speed
- 5-Year Warranty

Con 256GB Micro SD Surveillance



CTMS2256

- Up to 40,000 Hours Recording
- Perfect for 24x7 Surveillance
- Class 10 U3
- 100MB/s Speed
- 5-Year Warranty

CAMERA SPEAKER

Con CAMERA SPEAKER (DOME)



CT-DSP-001

- Two way Camera
- External Spk

Con CAMERA SPEAKER (BULLET)



CT-BSP-001

- Two way Camera
- External Spk

CABLE TESTER

Con Lan Cable Tester



CT-LT-468

- Tests RJ45 Ethernet and RJ11
- Telephone cables
- Detects open, short, miswired, and crossover connections
- Master & Remote Unit for efficient cable testing
- Quick and easy operation with clear
- LED indicators
- Compact, lightweight, and easy to carry
- Ideal for network installation, maintenance, and troubleshooting
- Powered by a 9V PP3 battery (not supplied)

SURVEILLANCE AWARDS

 **Consistent®**



CONSISTENT CELEBRATES VICTORY WITH
16th DT AWARDS 2024
FOR FASTEST GROWING INDIAN CCTV
BRAND



dt
DIGITAL TERMINAL
16TH DT AWARDS 2024
Fastest Growing Indian CCTV Brand
CONSISTENT

 www.consistent.in |  marketing@consistent.in


 **Consistent®**



CONSISTENT CELEBRATING VICTORY WITH
17TH NCN AWARDS 2024
FOR
THE BEST INDIAN IP CAMERA BRAND OF 2024



NCN
17TH NCN AWARDS 2024
The Best Indian IP Camera Brand of 2024
Consistent

 www.consistent.in |  marketing@consistent.in

 **Consistent®**



CONSISTENT CELEBRATING VICTORY WITH
17TH NCN AWARDS 2024
FOR THE HIGHEST SELLING MOTHERBOARD &
THE BEST INDIAN IP CAMERA BRAND OF 2024



NCN
17TH NCN AWARDS 2024
WINNER
Consistent

 www.consistent.in |  marketing@consistent.in

 **Consistent®**

BEST MADE IN INDIA SURVEILLANCE
BRAND



iTVoice
www.itvoice.in
iTawards Awarded to **CONSISTENT INFOSYSTEMS PVT. LTD.**
BEST MADE IN INDIA SURVEILLANCE BRAND
26TH Sep. 2024, New Delhi

Huge Congratulations to our amazing team
on this outstanding achievement!

N TRIPS

BANGKOK & VIETNAM TRIP 2025






Scan to View
Our Catalogue



Scan to Visit
Our Website



e-Store

Consistent Infosystems Private Limited

Corporate Office:

307, Shakuntala Building, 59, Nehru Place,
New Delhi 110 019. India.

Toll Free: 1800 103 4593

(9:00am to 6:00pm. Monday - Saturday.)

Email: info@consistent.in | Web: www.consistent.in



consistentinfosystems



consistent-india



consistentindia



consistentinfo1



Consistent Infosystems Pvt. Ltd.



+91 8929766306